



Typical Inspection Data:

| | |
|-----------------------|--------------|
| Density @ 20°C | 0.850 |
| Viscosity @ 100°C | 13.5 cSt |
| Viscosity @ 40°C | 78 cSt |
| Viscosity Index | 160 |
| Viscosity CCS @ -30°C | 6000 cP |
| T.B.N. | 7.2 mg KOH/g |
| Sulphated Ash Mass | 0.8% |
| Zinc | 0.10% |
| Calcium | 0.18% |
| Phosphorus | 0.09% |
| Colour | Brown |
| Flash Point | 230°C |
| Pour Point | -39°C |

PD Plus 5W-40

Fully Synthetic

Recommended by Comma for applications requiring:

VW 505 01, FORD WSS M2C917-A; VW 502 00, VW 505 00; BMW LL-04; MB 229.31
ACEA C3; API SN CF

Product Features:

- For VW PD/unit injector engines operating on fixed service intervals.
- Fully synthetic, high performance, 5W-40 oil, for vehicles fitted with the VW 'Pumpe Düse' PD or unit injector engine. Also protects exhaust after-treatment units.
- Do not mix this oil with other types of oil as the exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

22-05-2015